



StoberPel Enhancing Seal

PRODUCT DESCRIPTION

StoberPel Enhancing Seal is a high-performance, solvent-based impregnating agent designed to provide superior water repellency and aesthetic enhancement to masonry surfaces. Based on a reactive **Polymethylsilsesquioxane** resin it penetrates deep into the substrate to form a durable hydrophobic barrier while intensifying the natural color of the stone.

KEY FEATURES

- Deep penetration into porous substrates
- High active solids for superior "wet-look" enhancement
- Highly vapor permeable; allows substrate to "breathe"
- Fast-drying ethanol carrier for rapid return to service
- Excellent UV stability and weather resistance

TECHNICAL PROPERTIES

Property	Value
Active Content	Organosilicon Polymer
Carrier	Anhydrous Ethyl
Density	0.82 - 0.85 g/cm ³
Appearance	Clear to slightly amber liquid
Flash Point	~13°C
Full Cure	24 hours
Coverage Rate	4 - 8 m ² /L (Substrate dependent)

APPLICATION GUIDELINES

1. Substrate Preparation: Surface must be clean, dry (moisture content <5%), and free of coatings.
2. Application: Apply via low-pressure spray or brush. A 'wet-on-wet' application is recommended to ensure even enhancement.
3. Precautions: Do not apply in direct sunlight or if rain is expected within 4 hours. Product is moisture sensitive; keep container sealed when not in use.

- Packaging** 5L, 20L, 200L and 1000L
- Shelf life** 12 months from manufacturing date – store in cool and dry area and do not exceed temperatures of 35°C and R.H 80%
- Disposal** In accordance with all local and state laws for disposal.

Safety Classified Non dangerous goods material. It is recommended that the handling instructions outlined in the **Safety Data Sheet and label be followed.**
 Keep out of reach of children and pets.
 Avoid contact with eyes. In case of accidental eye contact, rinse thoroughly with water.
If swallowed, seek medical attention immediately and provide the label or Safety Data Sheet (SDS) to the medical professional.

FIRST AID: Eyes - If eye contact occurs, flush thoroughly with water and seek medical advice. Skin - If signs of swelling, rash or irritation occur on skin, wash area with soap and water and discontinue use. Swallowed - If swallowed rinse mouth out with water.

If needed, for advice, contact the Poisons Information Centre (**Australia 131 126, NZ 0800 764 766**) or contact your local doctor or hospital.

Limitations Not suitable for repairs on extremely deteriorated or structurally compromised concrete. Avoid applying on wet or damp surfaces. Always follow proper concrete repair procedures for optimal results.

The information provided in this Technical Data Sheet is based on our current knowledge and is intended to guide users in the application of **Stober Waterbased Penetrating Sealer**. However, as conditions and methods of use are beyond our control, users are encouraged to conduct their own tests to ensure suitability for their specific applications. No warranties, express or implied, are made.

For more information, contact our technical support team.





Technical Data sheet



Disclaimer

Anotec Environmental does not guarantee, and accepts no legal liability, for the accuracy, reliability, currency, or completeness of any material on this Technical Data Sheet or any related documents. You should seek appropriate independent professional advice before making any decisions based on material found on this technical datasheet or any related documents. The Customer is responsible for determining whether the products are fit for use and ensuring all local and state laws are followed in accordance to use and disposal.

NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

CONTACT INFORMATION:

Anotec Environmental
8 Nelson Avenue, Padstow, NSW, 2211
Australia
+61 (02) 9700 1222
technical@anotec.com.au

www.anotec.com.au

END OF DATASHEET

ANOTEC
ENVIRONMENTAL PTY LTD